



FIST-GPST-12

FIST generic patching shelf tray

FIST is a Fiber Infrastructure System Technology.

The Generic Patch/Splice Tray, FIST-GPST-12 is a mechanical tray assembly for the FIST fiber management system in a rack environment.

FIST-GPST-12's are typically used in conjunction with a FIST splice and patch shelf (FIST-GPS2).

The unit has the following functions and features

- Patching only, using patch cords, connectorized break-out or intra-facility cable
- Splicing loose tube cable, non connectorized intra-facility or break-out cable to pigtails and patching these pigtails to patch cords
- Splitters can be integrated
- Full patching capability on the tray and between the trays of one shelf.

Patching trays are used instead of front patch panels

- Patch cords are better managed in a horizontal plane
- Full access at both sides of the connection
- Reconnection to other positions in the same tray or shelf does not result in uncontrolled overlengths
- Various connector adapters possible
- Bend controls guide and protect the pigtail cable and ensure controlled cable bending
- Empty versions available as well as filled with various types of adapters/retainers and eventually pre-fibered with the conforming pigtails.

Dimensions, capacity

Description	Dimensions			Max. Capacity std. connectors	SFF connectors
	H mm	W mm	D mm		
FIST-GPST-12	18	355	190	12	24

Ordering information

FIST-GPST-12- X X X -2

Tray options

Trays are ordered per set of 2 complementary pieces (each set can hold 24 standard or 48 SFF fiber connections) with the following configuration:

Cable type	Pre-fibered	Splice holder holder or micro-fan-out	Patchcords leave shelf side			
			Left Std. connectors	Right Std. connectors	Left SFF connectors	Right SFF connectors
Patchcord or pre-connectorized BOC	No	-	AA	AA	AA	AA
Loose tube cable or non pre-connectorized IFC or non-preconnectorized BOC (3)	Yes (2)	SMOUV12 (1)	IA	AI	MA	AM
		ANT	JA	AJ	NA	AN
		RECORDsplice	VA	AV	WA	AW
	No	SMOUV12 (1)	EA	AE	PA	AP
	No	ANT	FA	AF	QA	AQ
		RECORDsplice	BA	AB	ZA	AZ
		RECORDsplice	BA	AB	-	-

- (1) Only for SMOUV-1120-02 (45 mm long heat-shrinkable splice protector) which is supplied with the kit.
- (2) Contact your local sales engineer for trays with pre-fibered pre-connectorized IFC.
- (3) BOC: Break-out cable (diameter of individual pigtails inside the BOC is max. 2.8 mm). GTU2 needs to be ordered separately.

Connector adapter with retainer

N No connectors/pigtails

Min.return loss	SC	FC	E2000	LC
Single mode standard				
45 dB (PC)				
50 dB (UPC)	A	C		L1
60 dB (APC 8°)	B	D	E9	L2
60 dB (APC 9°)	S3			
Single mode low loss				
50 dB (UPC)	S6			
60 dB (APC 8°)	S7		F	
60 dB (APC 9°)	S8			
Single mode consumer grade				
50 dB (UPC)	SC	FC		LC
60 dB (APC 8°)	SD	FD		LD

- In case of Multi-mode application order empty trays and loose adapters only
- In case of DIN/ST/MU adapter applications contact your local sales engineer

Consumables, accessories and tools

Refer to the ordering guide of FIST-GPS2 and cable assemblies for more information.

For more technical options and order quantity information, please consult the products ordering guides or your local sales representative.

Tyco Electronics, TE logo, FIST, SMOUV and RECORDsplice are trademarks.

The information given herein, including drawings, illustrations and schematics which are intended for illustration purposes only, is believed to be reliable. However, Tyco Electronics makes no warranties as to its accuracy or completeness and disclaims any liability in connection with its use. Tyco Electronics' obligations shall only be as set forth in Tyco Electronics' Standard Terms and Conditions of Sale for this product and in no case will Tyco Electronics be liable for any incidental, indirect or consequential damages arising out of the sale, resale, use or misuse of the product. Users of Tyco Electronics products should make their own evaluation to determine the suitability of each such product for the specific application.

Tyco Electronics Raychem bvba
Diestsesteenweg 692
3010 Kessel-Lo, Belgium
Tel 32-16 351 011 (USA)1-919-557-8900
Fax 32-16 351 697 (USA)1-919-557-8498
www.tycoelectronics.com
www.telecomosp.com
TC 528/DS/10 07/09