

accommodate the FIST fiber management system in a central office, head-end or customer premises environment.

FIST-GR3 is typically used to house connector panels and separate shelves for splicing, patching, equipment and devices. The rack is designed to allow proper management and storage of pigtail and patch cord overlengths

Features

Easy handling

- Less packaging waste
- Easy to transport, store, handle and install thanks to compact design
- Universal installation manual (drawings/no wording)

Flexibility

- Compatible with the TE FIST-GR2 range
- Compatible with the TE FIST-GSS2/GPS2 and FIST-GSS3/GPS3 range
- Available from stock
- Depth and width in accordance with ETSI

- ETSI mounting profiles with cage nuts for shelf mounting provided at the rear of the rack for optimal access from the front
- Possible horizontal and vertical patch cord management (HPM and VPM) for storage of functional patch cord overlength

All purpose rack

- Possible horizontal and vertical patch cord storage (HPS and VPS) for excess patch cord overlength between the shelves and either the equipment or adjacent racks
- Bend control on all fiber routing

- A structured division and distribution of the cable elements
- A wide variety of options
 - Cable attachment plates can be mounted in any location (top/bottom) in the side duct
 - Easy access to cables, pigtails and jumpers during installation, maintenance and upgrade
 - Easy adaptation to specific applications by changing the rack configuration, shelf configuration and routings of pigtails and jumpers
- Various mounting options
 - Wall mounting: stand alone or multiple side-to-side mounting (optional kit)
 - Back-to-back mounting



Dimensions and capacity (mm)

Description	Dimensions			Capacity		- :
	Н	W	D	Height units (ETSI)**	# FIST-3HU shelves	I
FIST-GR3	2200	*	300	80-8=72	14	_

The rack unit is painted (powder coated) in light grey (RAL-7035).

Ordering information

Basic rack

FIST-GR3-900-2 Rack of 900 mm, 150-ETSI-150 (side duct - main section - side duct)

FIST-GR3-1050-2 Rack of 1050 mm, 150-ETSI-300 or 300-ETSI-150 (side duct - main section - side duct)

FIST-GR3-1200-2 Rack of 1200 mm, 300-ETSI-300 (side duct - main section - side duct)

Accessory rack kits

Door kits

FIST-GR3-150-DOORKIT-2 $2 \times 150 \text{ mm}$ side duct doors FIST-GR3-300-DOORKIT-2 $2 \times 300 \text{ mm}$ side duct doors

FIST-GR3-900-DOORKIT-2 2 x 150 side duct doors & 600 mm central door FIST-GR3-1200-DOORKIT-2 2 x 300 mm side ducts doors & 600 mm central door

Roof kits

FIST-GR3-TOP-150 2 single roof plates for 150 mm side duct + mounting screws
FIST-GR3-TOP-300 2 single roof plates for 300 mm side duct + mounting screws
FIST-GR3-TOP-600 1 single roof plate for 600 mm main section + mounting screws

Panel kits

FIST-GR3-PANELKIT-2 1 set of 2 panels of 300 mm each for covering side or back + mounting screws

Other accessory kits

FIST-GR3-DL3 Cylinder lock for central door + locks for side ducts

FIST-GR3-STS 2 metal plates and mounting accessories

Depth extension kitssee ordering guideFront mounting kitsee ordering guideTransparent door kitsee ordering guide

Consumables, accessories and tools

See the ordering guides for FIST-GR3 and FIST-GSS3/GPS3.

For more technical options and order quantity information, please consult the products ordering guides or your local sales representative.

FIST, TE (logo) and TE Connectivity are trademarks of the TE Connectivity group of companies and its licensors.

The information given herein, including drawings, illustrations and schematics which are intended for illustration purposes only, is believed to be reliable. However, TE Connectivity makes no warranties as to its accuracy or completeness and disclaims any liability in connection with its use. TE Connectivity's obligations shall only be as set forth in TE Connectivity's Standard Terms and Conditions of Sale for this product and in no case will TE Connectivity be liable for any incidental, indirect or consequential damages arising out of the sale, resale, use or misuse of the product. Users of TE Connectivity products should make their own evaluation to determine the suitability of each such product for the specific application.

Tyco Electronics Raychem bvba
Diestsesteenweg 692
3010 Kessel-Lo, Belgium
Tel 32-16 351 011 (USA)1-919-557-8900
Fax 32-16 351 697 (USA)1-919-557-8498
www.te.com
www.telecomnetworks.com
TC 1054/DS/5 03/12



^{*} The width depends on the configuration - see ordering information.

^{**} The base duct included in the rack occupies 8 ETSI height units.