FIST-GR3F

FIST-GR3F, is an all purpose, easy to assemble metal rack designed to accommodate the FIST fiber management system in a central office, head-end or customer premises environment.

FIST-GR3F is typically used to house connector panels and separate shelves for splicing, patching, equipment and devices. The rack is designed to allow proper management and storage of pigtails and patch cord overlengths


Features

Easy handling

- · Less packaging waste
- Easy to transport, store, handle and install thanks to compact design
- Universal installation manual (drawings/no wording)

Flexibility

- Compatible with the TE Connectivity 15" version of FIST-GSS3/GPS3 range and FOMS-FPS-HD range
- Optimized for small footprint



 Possible horizontal and vertical patch cord management (HPM and VPM) for storage of functional patch cord overlength

All purpose rack

 Possible horizontal and vertical patch cord storage (HPS and VPS) for excess patch cord overlength between the shelves and either the equipment or the adjacent racks



- Bend control on all fiber routing
- A structured division and distribution of the cable elements
- A wide variety of options
 - Cable attachment plates can be mounted in any location (top/bottom) in the side duct
 - Easy access to cables, pigtails and jumpers during installation, maintenance and upgrade
 - Easy adaptation to specific applications by changing the rack configuration, shelf configuration and routings of pigtails and jumpers
- Various mounting options
 - Wall mounting: stand alone or multiple side-to-side mounting (optional kit)
 - Back-to-back mounting



Dimensions and capacity (mm)

| Description | Dimensions | | | Capacity | | |
|-------------|------------|---|-----|--------------|------------|---|
| | Н | W | D | Height units | # FIST-3HU | |
| | | | | (ETSI)** | shelves | |
| FIST-GR3F | 2200 | * | 300 | 80-8=72 | 14 | _ |

The rack unit is painted (powder coated) in light grey (RAL-7035).

* The width depends on the configuration - see ordering information.

** The base duct included in the rack occupies 8 ETSI height units.

Ordering information

Basic rack

| FIST-GR3F-600-2 | Rack of 600 mm, 150 - 15" or 15" - 150 |
|------------------------|---|
| FIST-GR3F-750-2 | Rack of 750 mm, 300 - 15" or 15" - 300 |
| FIST-GR3F-900-2 | Rack of 900 mm, 150 - 15" - 300 or 300 - 15" - 150 |
| FIST-GR3F-1050-2 | Rack of 1050 mm, 300 - 15" - 300 |
| Accessory rack kits | |
| Door kits | |
| FIST-GR3-150-DOORKIT-2 | 2 x 150 mm side duct doors |
| FIST-GR3-300-DOORKIT-2 | 2 x 300 mm side duct doors |
| Roof kits | |
| FIST-GR3-TOP-150 | 2 single roof plates for 150 mm side duct + mounting screws |
| FIST-GR3-TOP-300 | 2 single roof plates for 300 mm side duct + mounting screws |
| Panel kits | |
| FIST-GR3-PANELKIT-2 | 1 set of 2 panels for covering side + mounting accessories and installation instruction |
| Other accessory kits | |
| FIST-GR3-DL3 | Cylinder lock for central door + locks for side ducts |
| FIST-GR3-STS | 2 metal plates and mounting accessories |
| | |
| | |
| | |

Consumables, accessories and tools

See the ordering guides for FIST-GR3F, FIST-GSS3/GPS3 and FOMS-FPS-HD.

For more technical options and order quantity information, please consult the products ordering guides or your local sales representative.

FIST, TE (logo) and TE Connectivity are trademarks of the TE Connectivity group of companies and its licensors.

The information given herein, including drawings, illustrations and schematics which are intended for illustration purposes only, is believed to be reliable. However, TE Connectivity makes no warranties as to its accuracy or completeness and disclaims any liability in connection with its use. TE Connectivity's obligations shall only be as set forth in TE Connectivity's Standard Terms and Conditions of Sale for this product and in no case will TE Connectivity be liable for any incidental, indirect or consequential damages arising out of the sale, resale, use or misuse of the product. Users of TE Connectivity products should make their own evaluation to determine the suitability of each such product for the specific application.

Tyco Electronics Raychem bvba Diestsesteenweg 692 3010 Kessel-Lo, Belgium Tel 32-16 351 011 (USA)1-919-557-8900 Fax 32-16 351 697 (USA)1-919-557-8498 www.te.com www.telecomnetworks.com TC 1089/DS/3 04/12

