

TrueNet®

LSA Connection Boxes



A range of lightweight steel distribution boxes for LSA-PLUS® 10 pair modules.

Each of the standard 500 Series boxes is equipped with stainless steel backmount frames to support either 100, 200 or 400 pairs. Additional features include jumper rings as standard for tidy cable management; lockable doors with 180 degree access, doors can also be removed for installation and then hinged either right or left depending on the physical environment.

510, 520, 530 and 540 box support normal capacities of 340, 680, 1020 or 1340 pairs. This range also allows for an additional 50 pairs to be mounted under the standard verticals or 25 or 30 pair BT PO226 connectors with an additional 5 way backmount frame. As with the standard range these boxes utilise removable and lockable doors which also include a facility to store document wallets.

Features

- Manufactured from lightweight 1mm mild steel
- Removable top and bottom gland plates and internal jumper rings
- Quick release hinges
- Doors can be hinged either left or right

Benefits

- Strong, robust and durable solution
- Tidy cable management
- Quick release hinges aid and simplify installations
- Increased flexibility

TECHNICAL DATA



Technical Assistance:
Europe & Middle East
+32 2 712 6542
euro.tac@adckrone.com

www.adckrone.com

South Africa
+27 11 466 3333
infos@adckrone.com

United Kingdom
0800 960236
contactuk@adckrone.com

Ordering Information

Description	Pairs Capacity	Backmount Frames	Dimensions (mm) WxHxD	Weight (Kg)	Jumper rings	Pack Qty	Catalogue No.
Connection Box 500 Series	100	1x10 way	235x350x115	3.2	4	1	6428 2 421-00
Connection Box 500 Series	200	1x20 way	235x700x115	5.2	6	1	6428 2 420-00
Connection Box 500 Series	200	2x10 way	425x350x115	5.4	6	1	6428 2 418-00
Connection Box 500 Series	400	2x20 way	425x700x115	8.6	9	1	6428 2 419-00
Connection Box 510	340	1x34 way	300x1000x140	11	8	1	6428 2 423-00
Connection Box 520	680	2x34 way	500x1000x140	17	12	1	6428 2 424-00
Connection Box 530	1020	3x34 way	750x1000x140	25	16	1	6428 2 425-00
Connection Box 540	1340	4x34 way	1000x1000x140	32	20	1	6428 2 422-00

TECHNICAL DATA



Web Site: www.adckrone.com/en

UK Office: ADC Communications (UK) Ltd., Runnings Road, Kingsditch Trading Estate, Cheltenham, Gloucestershire GL51 9NQ, United Kingdom • Phone: +44 (0) 1242 264 400 Fax: +44 (0) 1242 264 488 contactuk@adckrone.com

South African Office: ADC Telecommunications (Africa) PTY Ltd., 16 Brand Hatch Close, Kyalami Business Park, Midrand, 1685, Johannesburg, South Africa • Phone: +27 11 466 3333 Fax: +27 11 466 3300 Email: infos@adckrone.com

EMEA Office: ADC GmbH, Beeskowdamm, 3-11, 14167 Berlin, Germany • Phone: +49 30 8453 1818 Fax: +49 30 8453 1703. For a listing of all ADC KRONE's global sales office locations, please refer to our web site.

Specifications published here are current as of the date of publication of this document. Because we are continuously improving our products, ADC KRONE reserves the right to change specifications without prior notice. At any time, you may verify product specifications by contacting ADC GmbH headquarters in Berlin. ADC Telecommunications, Inc. views its patent portfolio as an important corporate asset and vigorously enforces its patents.

Part Number 200402BE May 08 Original © 2008 ADC Communications (UK) Ltd. All Rights Reserved