



OFMC

Outdoor fiber micro-closure

The gel sealed in-line OFMC closure offers a mechanical and waterproof protection (IP 68) for fiber splices in the FTTH network (areal, manholes).

The housing is in two parts openable by using 2 long latches.

Cable entries are easily accessible and allow cable loop through configuration in combination with up to eight-drop cables. Depending on the configuration, the OFMC can be used as a track joint, a direct cable access or a loop through application.

The central base plate allows cables fixation and protection of the tube loop (micro sheet construction).

A hingeable splicing tray offers a perfect protection for the storage of bare fiber, of fiber splices and eventually of a splitter.

Features

- In-line compact closure
250 x 100 x 70 mm = 1,75 dm³
- Latch closing system
- Sealing made by compressing gel during closing
- Tool less product
- Compatible with RECORDsplice, SMOUV and ANT splice protectors
- Easy individual drop cable termination on strain relief device
- Main cable sealing from 4-10 mm
- Drop cable sealing from 4-6 mm
- The closure can be used as well in aerial, pedestal and underground (up to 2 meters) environment
- For G657 fibers only

Kit content

- Box with fiber organizer
- Main cable seal and termination device
- Drop cable seal for 8 drops with drop cable termination device

Ordering information

OFMC - I8 - XXX

S24	Splice tray for 24 splices with SMOUV
S48	Splice tray for 48 splices with SMOUV

Accessories

OFMC-KTU(100)	Kit of 100 cable termination devices
OFMC-MOBRA-01	Wall mount brackets

For more technical options and order quantity information, please consult the products ordering guides or your local sales representative.

RECORDsplice, SMOUV, TE (logo) and TE Connectivity are trademarks of the TE Connectivity group of companies and its licensors.

The information given herein, including drawings, illustrations and schematics which are intended for illustration purposes only, is believed to be reliable. However, TE Connectivity makes no warranties as to its accuracy or completeness and disclaims any liability in connection with its use. TE Connectivity's obligations shall only be as set forth in TE Connectivity's Standard Terms and Conditions of Sale for this product and in no case will TE Connectivity be liable for any incidental, indirect or consequential damages arising out of the sale, resale, use or misuse of the product. Users of TE Connectivity products should make their own evaluation to determine the suitability of each such product for the specific application.

Tyco Electronics Raychem bvba
Diestsesteenweg 692
3010 Kessel-Lo, Belgium
Tel 32-16 351 011 (USA)1-919-557-8900
Fax 32-16 351 697 (USA)1-919-557-8498
www.te.com
www.telecomnetworks.com
TC 1065/DS/3 11/11

