



FACT™ Fiber Optic Patch Panel, gray, 4E high, 192-port, singlemode, holding 8 hinged trays loaded with LC/APC adapters

- Designed for use with the all-purpose all-front-access FIST-GR3 fiber frames supporting up to 2,688 LC or 1,344 SC connections in a single frame
- Reduced installation and maintenance time via the toolless snap-on design supporting both interconnect and cross-connect applications
- Flexible customization enabled by 4 chassis types (patch-only, patch-splice, pre-cabled and splice-only) to support all ODF applications
- High density through the single FACT element height (1E) being 30% less tall compared to the industry standard panel height (1HU)

Product Classification

Brand	FACT™
Product Series	FACT
Product Type	Fiber patch panel
Regional Availability	Asia Australia/New Zealand EMEA Latin America North America

Dimensions

Depth	283.00 mm 11.14 in
Height	123.80 mm 4.87 in
Width	524.00 mm 20.63 in

Environmental Specifications

Flammability Rating	UL 94 V-0
Operating Temperature	-40 °C to +70 °C (-40 °F to +158 °F)
Storage Temperature	-20 °C to +85 °C (-4 °F to +176 °F)

General Specifications

Rack Units	2.8
Shelf Movement	Sliding
Application	Compatible with FIST-GR3-style frames
Body Style	Symmetrical
Color	Gray
Color, front	Gray
Functionality	Patching
Growth Configuration	Fully loaded
Includes	Mounting hardware
Interface Feature, front	APC
Interface, front	LC

Package Quantity	1
Patch Cord Routing	Left sided Right sided
Patching Capacity, maximum	192
Rack Type	EIA 19 in
Total Ports, quantity	192
Transmission Standards	ETSI EN 300 019-1-3 IEC 61300-3-30

Regulatory Compliance/Certifications

Agency	Classification
RoHS 2011/65/EU	Compliant
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system

