


**OPTICAL CABLES**  
**BLOWING CABLE**  
**H0385A**

**MCB 1610**

**Z**

**6fo - M6 - G657A1**

The MCB1610 range of micro-cables has been developed to be installed by blowing in micro-ducts towards the entrances of houses or feet of buildings. Its optimized dimension and its structure allow this cable to be installed in micro-ducts of small sizes either buried or installed in sheaths.



\*Principle cross section\*

- Loose Tube with filling compound for tightness
- Aramid yarns
- Outer sheath : HD polyéthylène NF EN 50290-2-24 Compliant


Fibre count		Modularity	Part number	Linear density		Outer sheath $\phi$		Sheath colour
6	fo	M6	H0385A	5	kg/km	2.5	mm	Black

Optical fibres colour code ①						
1 Red	2 Green	3 Blue	4 Yellow	5 White	6 Grey	

Modules colour code ①	
1 Natural	

Marking ①	Colour :	White
Example :	ACOME MCB1610 2021 50 6 FO G657A1 H0385 1500 m (Year) (Week)	

Packaging ①	Drum type	Dimensions			Total weight (kg)	Delivery length (m)
		Length (L) (mm)	Width (W) (mm)	Height (H) (mm)		
Drum	XC	600	326	600	25	4000
Drum	6 x XC	1200	800	790	165	24000



Cables are supplied with a protective wrap which must be maintained until full use of the product.

① For any other choice, please contact us.

**OPTICAL CABLES**  
**BLOWING CABLE**  
**H0385A**

**MCB 1610**

**Z**

**6fo - M6 - G657A1**

<b>Optical fibre /Datasheet (IEC 60793-2) :</b>	<b>G657A1</b>
---	---------------

<b>Cabled fibre attenuation :</b>	$\lambda = 1310 \text{ max} \leq 0,36 \text{ dB/km}$ $\lambda = 1550 \text{ max} \leq 0,22 \text{ dB/km}$ $\lambda = 1625 \text{ max} \leq 0,24 \text{ dB/km}$
-----------------------------------	--

<b>Characteristics</b>	<b>Values</b>	<b>Test method</b>
------------------------	---------------	--------------------

<b>Mechanical</b>			
Maximum Pulling Force	80	N	IEC 60794-1-21 E1
Crush resistance	300		
Reversibility of attenuation	0	N/cm	IEC 60794-1-21 E3
Bending radius (with tensile stress)	20x $\emptyset$	mm	IEC 60794-1-21 E6
Bending radius (without tensile stress)	15x $\emptyset$	mm	IEC 60794-1-21 E11

<b>Environmental</b>			
<b>Temperature range</b>			
- Transport and storage	-25 +70	°C	IEC 60794-1-22 F1
- Installation	-5 +40	°C	
- Operation	-20 +60	°C	
Water penetration	Compliant		IEC 60794-1-22 F5b/c

This documentation belongs exclusively to the company ACOME. Any reproduction, copies, extractions, modifications, etc., full or partial, are formally prohibited unless prior written permission from ACOME. Due to technical evolution, ACOME reserves the right, at any time and without notice, to modify the technical specifications announced for this product and/or to stop the manufacture of it unless contractual commitment. The ACOME mark is a

The guidelines for storage, transportation and cable installation are defined in our ACOPTIC guide:

<https://www.acome.com/en/The-Group/Library/Cable-Storage-Transport-and-Installation-rules>